HARMONY
Energy Lighting Solutions

LED RECESSED DOWNLIGHT

Hope 5

Product code: 10 01 IC DL 003




Hope 5 is a recessed LED downlight. With a die-cast aluminium housing and an opal diffuser, it offers IP44 protection and UGR<19 low glare. It is used for general and accent lighting in suspended ceilings of offices, shops, hotels and homes.

IP RATING	WARRANTY
IP44	**3 years**

IP 44 CE

DIMENSIONS (MM)



TECHNICAL DATA

IP rating	IP44
Mounting	Recessed
LED	Samsung, Bridgelux, Lumileds
Glare	UGR < 19
Driver	Philips, Osram, Tridonic, Eaglerise, Lifud
Input voltage	220–240 V AC / 50–60 Hz
LED lifetime	50,000 h (L80B10)
Dimensions	Ø139 mm
Cut-out	Ø 121 mm
Warranty	3 years
Origin	Türkiye

Technical values are subject to a ±10% tolerance. Efficacy is calculated by dividing luminous flux by nominal power. Harmony ELS reserves the right to make changes to products without prior notice.

Harmony ELS Energy Lighting Solutions
Adnan Kahveci Mahallesi Kuştepe Caddesi Onurkent Sitesi A4 Blok No:29/D 34528 Beylikdüzü / İstanbul
+90 538 428 9559 · info@harmonyels.com · harmonyels.com

HARMONY
Energy Lighting Solutions

Hope 5

Product code: 10 01 IC DL 003

CUSTOMISATION

DRIVER AND CONTROL

- Standard driver (on/off)
- DALI
- Wireless control

MOUNTING



Recessed

HOUSING COLOUR

01 White
03 Black
04 Grey
06 Any RAL colour

Up-to-date information and all options
https://harmonyels.com/en/product/hope-5

Technical values are subject to a ±10% tolerance. Efficacy is calculated by dividing luminous flux by nominal power. Harmony ELS reserves the right to make changes to products without prior notice.

Harmony ELS Energy Lighting Solutions
Adnan Kahveci Mahallesi Kuştepe Caddesi Onurkent Sitesi A4 Blok No:29/D 34528 Beylikdüzü / İstanbul
+90 538 428 9559 · info@harmonyels.com · harmonyels.com