

Lama Steel-Body Linear Luminaire

Product code: 20 01 IC ET 007



Lama Steel-Body Linear Luminaire is a vapour-proof LED luminaire. A sheet-steel linear luminaire only 25 mm high; 40 W, 3600 lm, 1200 mm, optional PIR sensor. With sheet steel body, white (RAL 9016) and uV-stabilised PC opal diffuser, it offers IP40 protection, Ra>80 colour rendering and 4000K / 6500K colour temperatures. It is used in offices, corridors, storerooms and plant rooms; it comes with a 3-year warranty.

POWER

40 W

LUMINOUS FLUX

3,600 lm

EFFICACY

90 lm/WCOLOUR
RENDERING**Ra > 80**

IP RATING

IP40

WARRANTY

3 yearsIP
40**CE**Ta
-10 / +65 °C**CRI>80**

KEY FEATURES

- 25 mm slim steel body, 1200 mm long
- UV-stabilised PC opal diffuser
- 40 W, 3600 lm
- Surface or pendant mounting
- Optional PIR sensor

DIMENSIONS (MM)

Dimension drawing in preparation

TECHNICAL DATA

IP rating	IP40
Housing	Sheet steel body, white (RAL 9016)
Mounting	Surface-mounted, Pendant
LED type	SMD mid-power LED
LED	Samsung, Bridgelux, Lumileds, Ledvance
Optics	UV-stabilised PC opal diffuser
Input voltage	220–230 V AC / 50 Hz
Ambient temperature	-10 / +65 °C
LED lifetime	50,000 h
Dimensions	1200 × 75 × 25 mm
Weight	0.4 kg
Warranty	3 years

Lama Steel-Body Linear Luminaire

Product code: 20 01 IC ET 007

LIGHT AND POWER OPTIONS

Code	LED	Power	Luminous flux	Efficacy	CCT	CRI
20 01 IC ET 007-40-840	Samsung, Bridgelux, Lumileds, Ledvance	40 W	3,600 lm	90 lm/W	4000K	Ra > 80

CUSTOMISATION

COLOUR TEMPERATURE

☐ 4000K☐ 6500K

DRIVER AND CONTROL

☒ Standard driver (on/off)

MOUNTING



Surface



Pendant

HOUSING COLOUR



01 White